



# K005 SELECT Furniture Polish Aerosol

## 1. IDENTIFICATION OF THE PREPARATION AND COMPANY

**PRODUCT CODE:** K005  
**PRODUCT NAME:** SELECT  
**MANUFACTURER:** Selden Research Limited  
Staden Lane  
Ashbourne Road  
Buxton  
Derbyshire  
SK17 9RZ

**TELEPHONE:** 01298 26226  
**FAX:** 01298 26540  
**EMAIL:** [safety@selden.co.uk](mailto:safety@selden.co.uk)

**Distributed by**  
Jaytrade Ltd  
Units 1- 4 Brocks Farm  
Twitty Fee  
Danbury  
Chelmsford  
Essex  
CM3 4PG  
Tel: 01245 224646  
Fax: 01245 225078

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME CAS No.:	EINECS Nr.:	CLASSIFICATION	CONTENT
ALIPHATIC DISTILLATE 265-150-3	64742-48-9	Xn;R65. R10,R66.	5-10 %
BUTANE 203-448-7	106-97-8	F+;R12	10-30 %
KEROSENE - NARROW CUT - NON AROMATIC	64742-47-8	Xn;R65. R66.	5-10 %

The full text for all R-Phrases are displayed in Section 16

## 3. HAZARDS IDENTIFICATION

**R12 Extremely flammable.**

**PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.**

## 4. FIRST AID MEASURES

**INHALATION:** Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.

**INGESTION:** Rinse mouth thoroughly. Drink plenty of water. Get medical attention.

**SKIN:** Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

**EYES:** Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Use:., Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

**SPECIAL FIRE FIGHTING PROCEDURES:** Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

**UNUSUAL FIRE & EXPLOSIVE HAZARDS:** Aerosol cans may explode in a fire.

## 6. ACCIDENTAL RELEASE MEASURES

**SPILL CLEAN UP METHODS:** Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. If leakage cannot be stopped, evacuate area.

**ENVIRONMENTAL PRECAUTIONS:** Any spillage needs to be contained and not allowed to enter water courses

## 7. HANDLING AND STORAGE

**USAGE PRECAUTIONS:** Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

**STORAGE PRECAUTIONS:** Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.



## K005 SELECT

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
BUTANE		WEL	600	750

#### PROTECTIVE EQUIPMENT:



### 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Aerosol		
COLOUR:	White		
ODOUR:	Strong fragrant (Leather/Lavender type)		
PHYSICAL DATA COMMENTS:	Information given relates to total aerosol container contents.		
DENSITY/SPECIFIC GRAVITY(g/ml)	0.803		
FLASH POINT (°C):	- 74	N/A.	
AUTO IGNITION TEMPERATURE (°C):	+ 405		
FLAMMABILITY LIMIT - LOWER(%):	1.8		
FLAMMABILITY LIMIT - UPPER(%):	10.0		

### 10. STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperature conditions.
CONDITIONS TO AVOID:	Avoid heat, flames and other sources of ignition. Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.
HAZARDOUS COMPOSITION PRODUCTS:	Fire creates:, Toxic gases/vapours/fumes of:, Carbon monoxide (CO). Carbon dioxide (CO2).

### 11. TOXICOLOGY INFORMATION

INHALATION:	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Gas or vapour displaces oxygen available for breathing (asphyxiant). Unconsciousness.
SKIN CONTACT:	No specific health warnings noted.
EYE CONTACT:	Irritation of eyes and mucous membranes.

### 12. ECOLOGICAL INFORMATION

ECOTOXICITY:	Not classed as Hazardous to the Environment but release to the environment should be avoided.
--------------	---

### 13. DISPOSAL CONSIDERATIONS

DISPOSABLE METHODS:	Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.
---------------------	--

### 14. TRANSPORT INFORMATION

UN No ROAD:	1950
UK ROAD TRANSPORT CLASS:	-
ADR CLASS NO.:	2.1
PROPER SHIPPING NAME I:	AEROSOLS, FLAMMABLE
UN No SEA:	1950
IMDG CLASS:	2
UN NO. AIR:	1950
ICAO CLASS:	2.1



## K005 SELECT

### 15. REGULATORY INFORMATION

**LABEL FOR SUPPLY:**



**RISK PHRASES:**

R12 Extremely flammable.

**SAFETY PHRASES:**

S2 Keep out of the reach of children, S16 Keep away from sources of ignition - No smoking. S23 Do not breathe vapour/spray. S51 Use only in well-ventilated areas.

**STATUTORY INSTRUMENTS:**

Control of Substances Hazardous to Health. Chemicals (Hazard Information and Packaging) Regulations.

**APPROVED CODE OF PRACTICE:**

Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES:**

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

### 16. OTHER INFORMATION

**USER NOTES:**

The following risk phrases relate to the raw materials in the product and not the product itself:-

**REVISION DATE:**

05/04/2006

**REV. NO./REPL. SDS GENERATED:**

13

**R-PHRASES (Full Text):**

R12 Extremely flammable.| R10 Flammable., R66 Repeated exposure may cause skin dryness or cracking., R65 Harmful: may cause lung damage if swallowed.| R66 Repeated exposure may cause skin dryness or cracking., R65 Harmful: may cause lung damage if swallowed.|